

HQI-TS 150 W/WDL RX7S-24

POWERSTAR HQI-TS EXCELLENCE | Metal halide lamps with quartz technology for enclosed luminaires



- Shop interiors, shop windows
- Shopping arcades
- Foyers, reception areas
- Buildings, monuments, bridges
- Museums, exhibitions
- Exhibition halls and trade fairs
- Pedestrian zones, public squares
- Parks and gardens

Product benefits

- High efficiency
- Uniform distribution of light
- Good to excellent color rendering
- Long life time
- Hot restrike capable

Product features

- POWERSTAR quartz technology
- UV filter technology
- Light colors: warm white (WDL), neutral white (NDL), daylight (D), cool daylight (CD)
- Average life: 12,000 hours



Technical data

Electrical data

| | |
|--|--------------------------|
| Nominal wattage | 150 W |
| PFC capacitor at 50 Hz | 20 μ F ¹⁾ |
| Lamp current | 1.8 A |
| Rated wattage | 150 W |
| Rated lamp efficacy (standard condition) | 80 lm/W |


¹⁾ At rated voltage and $\cos \varphi \geq 0.9$

Light technical data

| | |
|--------------------------|----------|
| Luminous flux | 12000 lm |
| Color rendering index Ra | 75 |
| Color rendering group | 2A |
| Color temperature | 3000 K |
| Luminous efficacy | 83 lm/W |

Dimensions & weight

| | |
|---------------------------|----------|
| Diameter | 23.0 mm |
| Length | 135.0 mm |
| Light center length (LCL) | 66.0 mm |



Product line drawing with letters

Colors & materials

| | |
|----------------------|---------|
| Mercury-free | No |
| Lamp mercury content | 16.7 mg |

Temperatures


| | |
|-------------------------------------|--------|
| Maximum permitted pinch temperature | 350 °C |
|-------------------------------------|--------|

Lifespan

| | |
|--------------|---------|
| Lifespan B50 | 12000 h |
|--------------|---------|

Additional product data

| | |
|-----------------------------|-------|
| Base (standard designation) | RX7s |
| Design / version | Clear |



Spectral power distribution

Capabilities


| | |
|-------------------------|-----|
| Dimmable | No |
| Burning position | p45 |

Country specific categorizations

| | |
|--------------|------------------------------------|
| ILCOS | MD/UB-150/30/2A-H-RX7s=24-23/132/H |
|--------------|------------------------------------|


System guarantee

For the vast majority of our lamps we are offering an extended system guarantee in conjunction with OSRAM POWERTRONIC control gear.




Variation possibilities of the Colour Temperature

| | | T_n | CRI |
|-----------------------|-----|------------|-------|
| Daylight | D | > 5300 K | ≥90 |
| Neutral White | N | ca. 4000 K | 60-69 |
| Neutral White de luxe | NDL | 4200 K | ≥80 |
| Warm White de luxe | WDL | 3000 K | ≥80 |




Others graphics

Circuit diagram



Circuit diagram



Circuit diagram

Logistical Data

| Product code | Packaging unit (Pieces/Unit) | Dimensions (height x width x length) | Gross weight | Volume |
|---------------|---------------------------------|---|--------------|----------------------|
| 4008321678362 | Folding carton box 1 | 35 mm x 35 mm x 141 mm | 36.00 g | 0.17 dm ³ |
| 4008321678379 | Shipping carton box 12 | 123 mm x 159 mm x 154 mm | 498.00 g | 3.01 dm ³ |

References / Links

For more information on the system guarantee and the terms and conditions of the guarantee visit

▶ www.osram.com/system-guarantee

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.